

TECHNICAL DATA SHEET

Novatik® | METAL


CLICK S

Novatik METAL CLICK S system is considered to be the closest option to the traditional metal roof. That is why Novatik METAL CLICK S is the best solution both for reroofing or ultra-modern architectures. The shape, the dimensions and the falz assure a lower cost, without compromising the technical performances necessary for a high quality roofing system. Standing seam roof Novatik METAL CLICK S is fixed with stainless steel clamps, an option with an improved dilatation behavior.

>LAYERS

finishing MAT/HIGH COAT/FROST

1. **MAT:** Polyester Mat 40/35 µm;
HIGH COAT: Polyurethan - Polyamid 50 µm;
FROST: Polyurethan 60 µm;
(on the front side of the tile);
2. Primer;
3. Protective layer of: Zn / ZnMg;
4. Steel;
5. Protective layer of : Zn / ZnMg;
6. **MAT:** Polyester 10 µm;
HIGH COAT: Epoxid 10 µm;
FROST: Epoxid 12 µm;
(on the back side of the tile).




	Novatik® METAL CLICK S MAT	Novatik® METAL CLICK S HIGH COAT	Novatik® METAL CLICK S FROST
TOTAL LENGTH	1000 - 6000 mm	1000 - 6000 mm	1000 - 6000 mm
WIDTH OF COVER	530 / 386 mm	530 / 386 mm	530 / 386 mm
ROOF PITCH	Min. 8° *	Min. 8° *	Min. 8° *
THICKNESS (STEEL + ORGANIC COATINGS)	0,50/0,60 mm	0,51 mm	0,50 mm
LOOK	MAT	GLOSSY	CRYSTALLIZED
SURFACE COATING	Polyester Mat 40/35 microns , on the front side of the tile	Polyurethan/Polyamid 50 microns , on the front side of the tile	Polyurethan 60 microns on the front side of the tile
PROTECTION LAYER	Lack polyester 10 microns on the back side of the tile	Lack Epoxid 10 microns , on the back side of the tile	Lack Epoxid 12 microns , on the back side of the tile
RAW MATERIAL	Steel with protective coating of Zn 275 g/sqm /ZnMg 120g/sqm	Steel with protective coating of Zn 275 g/sqm	Steel with protective coating of Zn 275 g/sqm
UV RESISTANCE	RUV 4	RUV 4	RUV 4
CORROSION RESISTANCE	RC 3	RC 4	RC 4
FALTZ HEIGHT	25,4 mm	25,4 mm	25,4 mm


Panel dimensions: the values are defined with the acceptable tolerances according to SR EN 508-1:2009.

* For a roof pitch between 8° and 10°, the distance between the ridge and the eaves must be maximum 6 m long, without breakthroughs and without vertical overlaps.

	WIDTH OF COVER (mm)	TOTAL LENGTH (mm)	FALTZ HEIGHT (mm)
Click S 386	386	393	254
Click S 530	530	537	254



Novatik®
METAL | CLICK S MAT



0.5 mm

0.6 mm

20
YEARS

30
YEARS

AESTHETIC
WARRANTY

TECHNICAL
WARRANTY

20
YEARS


40
YEARS

AESTHETIC
WARRANTY

TECHNICAL
WARRANTY

* subject to availability

Novatik®
METAL | CLICK S HIGH COAT




20
YEARS

AESTHETIC
WARRANTY

40
YEARS

TECHNICAL
WARRANTY

Novatik®
METAL | CLICK S FROST



20
YEARS

AESTHETIC
WARRANTY


40
YEARS

TECHNICAL
WARRANTY

COLOURS 0,5 mm




COLOURS 0,6 mm



COLOURS



COLOURS



Manufactured by: NOVATIK SRL

HEAD QUARTERS: 9 Mai street, no. 75, Băicoi, Prahova, Tel: +40 244 260 140; Fax: +40 244 260 145; office@novatik.ro, novatik.ro
Novatik METAL CLICK S Technical Data Sheet – ENG_V3 | March 2025