

TECHNICAL DATA SHEET

Novatik® | METAL


CLICK

Novatik METAL CLICK system is considered to be the closest option to the traditional metal roof. That is why Novatik METAL CLICK is the best solution both for reroofing or ultra-modern architectures. The shape, the dimensions and the falz assure a lower cost, without compromising the technical performances necessary for a high quality roofing system. Standing seam roof Novatik METAL CLICK is fixed with screws.

>LAYERS

finishing MAT/HIGH COAT/FROST

1. **MAT:** Polyester Mat 40/35 µm;
HIGH COAT: Polyurethan - Polyamid 50 µm;
FROST: Polyurethan 60 µm;
(on the front side of the tile);
2. Primer;
3. Protective layer of: Zn / ZnMg;
4. Steel;
5. Protective layer of: Zn / ZnMg;
6. **MAT:** Polyester 10 µm;
HIGH COAT: Epoxid 10 µm;
FROST: Epoxid 12 µm;
(on the back side of the tile).




	Novatik® METAL CLICK MAT	Novatik® METAL CLICK HIGH COAT	Novatik® METAL CLICK FROST
TOTAL LENGTH	1000 - 6000 mm	1000 - 6000 mm	1000 - 6000 mm
WIDTH OF COVER	588 / 500 / 356 mm	588 / 500 / 356 mm	588 / 500 / 356 mm
ROOF PITCH	Min. 8° *	Min. 8° *	Min. 8° *
THICKNESS (STEEL + ORGANIC COATINGS)	0,50/0,60 mm	0,51 mm	0,50 mm
LOOK	MAT	GLOSSY	CRYSTALLIZED
SURFACE COATING	Polyester Mat 40/35 microns , on the front side of the tile	Polyurethan/Polyamid 50 microns , on the front side of the tile	Polyurethan 60 microns , on the front side of the tile
PROTECTION LAYER	Lack polyester 10 microns , on the back side of the tile	Lack Epoxid 10 microns , on the back side of the tile	Lack Epoxid 12 microns , on the back side of the tile
RAW MATERIAL	Steel with protective coating of Zn 275 g/sqm /ZnMg 120g/sqm	Steel with protective coating of Zn 275 g/sqm	Steel with protective coating of Zn 275 g/sqm
UV RESISTANCE	RUV 4	RUV 4	RUV 4
CORROSION RESISTANCE	RC 3	RC 4	RC 4
FALTZ HEIGHT	25,4 mm	25,4 mm	25,4 mm


Panel dimensions: the values are defined with the acceptable tolerances according to SR EN 508-1:2009.

* For a roof pitch between 8° and 12°, the distance between the ridge and the eaves must be maximum 6 m long, without breakthroughs and without vertical overlaps.

	WIDTH OF COVER (MM)	TOTAL LENGTH (MM)	FALTZ HEIGHT (MM)
Click 356	356	389	25,4
Click 500	500	533	25,4
Click 588	588	621	25,4



Novatik®
METAL | CLICK MAT



0.5 mm

0.6 mm

20 **30**


YEARS YEARS
AESTHETIC TECHNICAL
WARRANTY WARRANTY

20 **40**

YEARS YEARS
AESTHETIC TECHNICAL
WARRANTY WARRANTY

* subject to availability

Novatik®
METAL | CLICK HIGH COAT



20 **40**

YEARS YEARS
AESTHETIC TECHNICAL
WARRANTY WARRANTY

Novatik®
METAL | CLICK FROST




20 **40**

YEARS YEARS
AESTHETIC TECHNICAL
WARRANTY WARRANTY

COLOURS 0,5 mm

COLOURS 0,6 mm



COLOURS



COLOURS



Manufactured by: NOVATIK SRL

HEAD QUARTERS: 9 Mai street, no. 75, Băicoi, Prahova, Tel: +40 244 260 140; Fax: +40 244 260 145; office@novatik.ro, novatik.ro
Novatik METAL CLICK Technical Data Sheet – ENG_V3 | March 2025