

TECHNICAL DATA SHEET

Novatik | METAL

CLASSIC DUO

The bimodular design and symmetry of Novatik METAL CLASSIC DUO makes it one of the most effective types of metal roofing, which ensures easy and quick installation, minimizing technological losses. Based on elegance and refinement, classic remains a universal and timeless style, adaptable to any project. Although Novatik METAL CLASSIC DUO keeps all the style characteristics, it also enjoys the modern roofing technology, offering to users, besides a perfectly harmonized appearance, safety through durability.

>LAYERS

finishing MAT/HIGH COAT/FROST

1. **MAT:** Polyester Mat 35 µm;
HIGH COAT: Polyurethan - Polyamid 50 µm;
FROST: Polyurethan 60 µm;
(on the front side of the tile);
2. Primer;
3. Protective layer of: ZnMg / Zn
4. Steel;
5. Protective layer of : ZnMg / Zn;
6. **MAT:** Polyester 10 µm / 7 µm;
HIGH COAT: Epoxid 10 µm;
FROST: Epoxid 12 µm;
(on the back side of the tile).



Novatik | METAL | CLASSIC DUO MAT



0.5 mm		0.6 mm	
20	30	20	40
YEARS	YEARS	YEARS	YEARS
AESTHETIC WARRANTY	TECHNICAL WARRANTY	AESTHETIC WARRANTY	TECHNICAL WARRANTY

Novatik | METAL | CLASSIC DUO HIGH COAT



20	40
YEARS	YEARS
AESTHETIC WARRANTY	TECHNICAL WARRANTY

Novatik | METAL | CLASSIC DUO FROST



20	40
YEARS	YEARS
AESTHETIC WARRANTY	TECHNICAL WARRANTY

COLOURS 0,5 mm COLOURS 0,6 mm

BLACK RAL 9005	GREY RAL 7016	BROWN RAL 8017	BLACK RAL 9005
BROWN RAL 8019	BRICK RAL 8004	RED RAL 3009	GREY RAL 7016

COLOURS

BLACK RAL 9005	GREY RAL 7016

COLOURS

BLACK RAL 9005	GREY RAL 7016

	Novatik METAL CLASSIC DUO MAT	Novatik METAL CLASSIC DUO HIGH COAT	Novatik METAL CLASSIC DUO FROST
TOTAL LENGTH	1 340 mm	1 340 mm	1 340 mm
LENGTH OF COVER	1 260 mm	1 260 mm	1 260 mm
WIDTH OF COVER	740 mm	740 mm	740 mm
TILES/SQM	1,07 modules	1,07 modules	1,07 modules
ROOF PITCH	Min. 12°	Min. 12°	Min. 12°
THICKNESS (STEEL + ORGANIC COATINGS)	0,50/0,60 mm	0,51 mm	0,50 mm
WEIGHT / SQM	4,74 kg/sqm	4,96 kg/sqm	4,96 kg/sqm
LOOK	MAT	GLOSSY	CRYSTALLIZED
SURFACE COATING	Polyester Mat 35 microns , on the front side of the tile	Polyurethan/Polyamid 50 microns , on the front side of the tile	Polyurethan 60 microns on the front side of the tile
PROTECTION LAYER	Lack polyester 10 microns / 7 microns , on the back side of the tile	Lack Epoxid 10 microns , on the back side of the tile	Lack Epoxid 12 microns , on the back side of the tile
RAW MATERIAL	Steel with protective coating of ZnMg 120g/sqm /Zn 275 g/sqm	Steel with protective coating of Zn 275 g/sqm /ZnMg 120 g/sqm	Steel with protective coating of Zn 275 g/sqm
UV RESISTANCE	RUV 4	RUV 4	RUV 4
CORROSION RESISTANCE	RC 3	RC 4	RC 4

Manufactured by: NOVATIK SRL

HEAD QUARTERS: 9 Mai street, no. 75, Băicoi, Prahova, Tel: +40 244 260 140; Fax: +40 244 260 145; office@novatik.ro, novatik.ro
Novatik METAL CLASSIC DUO Technical Data Sheet – ENG_V2 | January 2023