

TECHNICAL DATA SHEET

Novatik® | METAL


CLICK S

Novatik METAL CLICK S system is considered to be the closest option to the traditional metal roof. That is why Novatik METAL CLICK S is the best solution both for reroofing or ultra-modern architectures. The shape, the dimensions and the falz assure a lower cost, without compromising the technical performances necessary for a high quality roofing system. Standing seam roof Novatik METAL CLICK S is fixed with stainless steel clams, an option with an improved dilatation behavior.

>LAYERS

finishing MAT/HIGH COAT/FROST


1. **MAT:** Polyester Mat 35 µm;
HIGH COAT: Polyurethan - Polyamid 50 µm;
FROST: Polyurethan 60 µm;
(on the front side of the tile);
2. Primer;
3. Protective layer of: ZnMg / Zn
4. Steel;
5. Protective layer of: ZnMg / Zn;
6. **MAT:** Polyester 10 µm / 7 µm;
HIGH COAT: Epoxid 10 µm;
FROST: Epoxid 12 µm;
(on the back side of the tile).



	Novatik® METAL CLICK MAT	Novatik® METAL CLICK HIGH COAT	Novatik® METAL CLICK FROST
TOTAL LENGTH	1000 - 6000 mm	1000 - 6000 mm	1000 - 6000 mm
WIDTH OF COVER	530 / 386 mm	530 / 386 mm	530 / 386 mm
ROOF PITCH	Min. 8° *	Min. 8° *	Min. 8° *
THICKNESS	0,50/0,60 mm	0,51 mm	0,50 mm
LOOK (STEEL + ORGANIC COATINGS)	MAT	GLOSSY	CRYSTALLIZED
SURFACE COATING	Polyester Mat 35 microns , on the front side of the tile	Polyurethan/Polyamid 50 microns , on the front side of the tile	Polyurethan 60 microns on the front side of the tile
PROTECTION LAYER	Lack polyester 10 microns / 7 microns , on the back side of the tile	Lack Epoxid 10 microns , on the back side of the tile	Lack Epoxid 12 microns , on the back side of the tile
RAW MATERIAL	Steel with protective coating of ZnMg 120g/sqm /Zn 275 g/sqm	Steel with protective coating of Zn 275 g/sqm /ZnMg 120 g/sqm	Steel with protective coating of Zn 275 g/sqm
UV RESISTANCE	RUV 4	RUV 4	RUV 4
CORROSION RESISTANCE	RC 3	RC 4	RC 4
FALTZ HEIGHT	25,4 mm	25,4 mm	25,4 mm

* For a roof pitch between 8° and 10°, the distance between the ridge and the eaves must be maximum 6 m long, without breakthroughs and without vertical overlaps.

	WIDTH OF COVER (mm)	TOTAL LENGTH (mm)	FALTZ HEIGHT (mm)
Click S 396	386	393	25,4
Click S 530	530	537	25,4



Novatik®
METAL | CLICK S MAT

0.5 mm 0.6 mm

20 YEARS AESTHETIC WARRANTY	30 YEARS TECHNICAL WARRANTY	20 YEARS AESTHETIC WARRANTY	40 YEARS TECHNICAL WARRANTY
--	--	--	--

Novatik®
METAL | CLICK S HIGH COAT

20 YEARS AESTHETIC WARRANTY	40 YEARS TECHNICAL WARRANTY
--	--

Novatik®
METAL | CLICK S FROST

20 YEARS AESTHETIC WARRANTY	40 YEARS TECHNICAL WARRANTY
--	--

COLOURS 0,5 mm			COLOURS 0,6 mm	
BLACK RAL 9005	GREY RAL 7016	BROWN RAL 8017	BLACK RAL 9005	GREY RAL 7016
BROWN RAL 8019	BRICK RAL 8004	RED RAL 3009	GREY RAL 7016	

COLOURS	
BLACK RAL 9005	GREY RAL 7016

COLOURS	
BLACK RAL 9005	GREY RAL 7016

Manufactured by: NOVATIK SRL

HEAD QUARTERS: 9 Mai street, no. 75, Băicoi, Prahova, Tel: +40 244 260 140; Fax: +40 244 260 145; office@novatik.ro, novatik.ro
Novatik METAL CLICK S Technical Data Sheet – ENG_V2 | January 2023