

# TECHNICAL DATA SHEET

Novatik | METAL

## CLICK SILENT

Novatik METAL CLICK SILENT – is a simple and rewarding solution for building acoustics improvement. Standing seam roof Novatik METAL CLICK SILENT - is improved in terms of sound insulation with a self-adhesive absorbent membrane designed for metallic constructions. It reduces the noise produced by rain and offers a maximum absorption of broadband sound from an enclosure. The membrane on the Novatik METAL CLICK SILENT works as an insulation layer against the noise produced by rain.

### >LAYERS

finishing MAT/HIGH COAT/FROST

1. **MAT:** Polyester Mat 35 µm;  
**HIGH COAT:** Polyurethan - Polyamid 50 µm;  
**FROST:** Polyurethan 60 µm;  
(on the front side of the tile);
2. Primer;
3. Protective layer of: ZnMg / Zn
4. Steel;
5. Protective layer of : ZnMg / Zn;
6. **MAT:** Polyester 10 µm / 7 µm;  
**HIGH COAT:** Epoxid 10 µm;  
**FROST:** Epoxid 12 µm;  
(on the back side of the tile).





Novatik | METAL  
CLICK SILENT MAT

Novatik | METAL  
CLICK SILENT HIGH COAT

Novatik | METAL  
CLICK SILENT FROST

TOTAL LENGTH	1000 - 6000 mm	1000 - 6000 mm	1000 - 6000 mm
WIDTH OF COVER	588 mm	588 mm	588 mm
ROOF PITCH	Min. 8° *	Min. 8° *	Min. 8° *
THICKNESS	0,50/0,60 mm	0,51 mm	0,50 mm
LOOK (STEEL + ORGANIC COATINGS)	MAT	GLOSSY	CRYSTALLIZED
SURFACE COATING	Polyester Mat <b>35 microns</b> , on the front side of the tile	Polyurethan/Polyamid <b>50 microns</b> , on the front side of the tile	Polyurethan <b>60 microns</b> on the front side of the tile
PROTECTION LAYER	Lack polyester <b>10 microns / 7 microns</b> , on the back side of the tile	Lack Epoxid <b>10 microns</b> , on the back side of the tile	Lack Epoxid <b>12 microns</b> , on the back side of the tile
RAW MATERIAL			
UV RESISTANCE	Steel with protective coating of <b>ZnMg 120g/sqm /Zn 275 g/sqm</b>	Steel with protective coating of <b>Zn 275 g/sqm /ZnMg 120 g/sqm</b>	Steel with protective coating of <b>Zn 275 g/sqm</b>
	RUV 4	RUV 4	RUV 4
CORROSION RESISTANCE	RC 3	RC 4	RC 4
FALTZ HEIGHT	25,4 mm	25,4 mm	25,4 mm

\* For a roof pitch between 8° and 12°, the distance between the ridge and the eaves must be maximum 6 m long, without breakthroughs and without vertical overlaps.



Novatik | METAL | CLICK SILENT MAT



0.5 mm      0.6 mm

20  
YEARS

30  
YEARS

20  
YEARS

40  
YEARS


AESTHETIC WARRANTY

TECHNICAL WARRANTY

AESTHETIC WARRANTY

TECHNICAL WARRANTY

Novatik | METAL | CLICK SILENT HIGH COAT



20  
YEARS

40  
YEARS

AESTHETIC WARRANTY

TECHNICAL WARRANTY

Novatik | METAL | CLICK SILENT FROST



20  
YEARS

40  
YEARS

AESTHETIC WARRANTY


TECHNICAL WARRANTY

COLOURS 0,5 mm

COLOURS 0,6 mm

COLOURS

COLOURS



Manufactured by: NOVATIK SRL

HEAD QUARTERS: 9 Mai street, no. 75, Băicoi, Prahova, Tel: +40 244 260 140; Fax: +40 244 260 145; office@novatik.ro, novatik.ro  
Novatik METAL CLICK SILENT Technical Data Sheet – ENG\_V2 | January 2023